

# Install and Configure a Shibboleth IdP v4.x on Debian-Ubuntu Linux with Apache2 + Jetty9

## Table des matières

1	Procédures sources.....	3
2	Install Instructions.....	3
2.1	Install software requirements.....	3
2.1.1	Update packages.....	3
2.1.2	Install the required packages.....	3
2.1.3	Install Amazon Corretto JDK.....	3
2.1.4	Check that Java is working.....	3
2.2	Configure the environment.....	3
2.2.1	Set the IdP hostname.....	4
2.2.2	Set the variable JAVA_HOME in /etc/environment.....	4
2.3	Install Shibboleth Identity Provider v4.x.....	4
2.4	Install Jetty 9 Web Server.....	5
2.4.1	Installation.....	5
2.5	Configuration Instructions.....	6
2.5.1	Configure Jetty.....	6
2.5.2	Configure SSL on Apache2 (front-end of Jetty).....	7
3	Configure Shibboleth Identity Provider Storage.....	8
4	Configuration de Shibboleth.....	9
4.1	Configuration des metadatas.....	9
4.2	Installer les certificats Belnet et eduGain.....	9
4.2.1	Certificat BELNET.....	9
4.2.2	Certificat eduGain.....	9
4.3	Configurer les « metadata providers ».....	10
5	Using SAML Proxying in the Shibboleth IdP to connect with Azure AD.....	12
5.1	Overview.....	13
5.2	IdP Proxying: Appearances and Perspectives.....	13
5.3	Implementing the Solution.....	14
5.3.1	Prerequisites.....	14
5.3.2	Terms and Settings.....	14
5.4	Steps and Tasks.....	15
5.4.1	Trust Task: 1. Update your IdP's metadata.....	15
5.4.2	Envoyer le fichier idp-metadata.xml à Belnet.....	16
5.4.3	Trust Task: 2. Register your IdP with Azure AD.....	16

5.4.4	Trust Task: 3. Register the upstream IdP's metadata locally.....	17
5.5	Configure the IdP for Proxing Behaviour.....	20
5.5.1	Proxy Task 1. Change the IdP authentication flow to SAML.....	20
5.5.2	Proxy Task 2. Update Your Attribute Filter.....	21
5.5.3	Proxy Task 3. Enable IdP to Recognize Azure AD Claims.....	21
5.5.4	Proxy Task 4. Subject Canonicalisation.....	28
5.5.5	Proxy Task 5. Configuring Attribute pass-through and/or hybrid resolving.....	29
5.5.6	Proxy Task 6. Handling REFEDS AuthnContext Requests (optional).....	30
5.6	Configure Shibboleth Identity Provider to release the persistent NameID.....	32
5.7	Configure Shibboleth Identity Provider to release the eduPersonTargetedID.....	33
5.8	Releaser les attributs.....	35
5.8.1	Les attributs récupérés d'Azure AD et mappés directement.....	35
5.8.2	Les attributs statiques.....	37
5.8.3	Les attributs mappés.....	40
5.8.4	Les attributs scriptés sur base d'autres attributs.....	41
5.8.5	Les attributs scriptés/transformés sur base de l'appartenance à des groupes.....	43
6	Renommer un IDP.....	51
7	Annexes.....	51
7.1	Annexe 1 : Contenu du fichier idp.yourdomain.be.conf pour Apache.....	51

# 1 Procédures sources

1. <https://github.com/ConsortiumGARR/idem-tutorials/blob/master/idem-fedops/HOWTO-Shibboleth/Identity%20Provider/Debian-Ubuntu/HOWTO%20Install%20and%20Configure%20a%20Shibboleth%20IdP%20v4.x%20on%20Debian-Ubuntu%20Linux%20with%20Apache2%20%2B%20Jetty9.md#install-jetty-9-web-server>

2. Using SAML Proxying in the Shibboleth IdP to connect with Azure AD:

<https://wiki.shibboleth.net/confluence/display/KB/Using+SAML+Proxying+in+the+Shibboleth+IdP+to+connect+with+Azure+AD#UsingSAMLProxyingintheshibbolethIdPtoconnectwithAzureAD-TrustTask:4.ConfigureAzureADAttributeReleaseTotheShibbolethIdP>

## 2 Install Instructions

### 2.1 Install software requirements

#### 2.1.1 Update packages

```
# apt update && apt-get upgrade -y --no-install-recommends
```

#### 2.1.2 Install the required packages

```
# apt install vim wget gnupg ca-certificates openssl apache2 ntp libservlet3.1-java liblogback-java --no-install-recommends
```

#### 2.1.3 Install Amazon Corretto JDK

```
# wget -O- https://apt.corretto.aws/corretto.key | sudo apt-key add -
```

```
# apt-get install software-properties-common
```

```
# add-apt-repository 'deb https://apt.corretto.aws stable main'
```

```
# apt-get update; sudo apt-get install -y java-11-amazon-corretto-jdk
```

```
# java -version
```

#### 2.1.4 Check that Java is working

```
# update-alternatives --config java
```

(It will return something like this "There is only one alternative in link group java (providing /usr/bin/java):")

### 2.2 Configure the environment

Be sure that your firewall is not blocking the traffic on port 443 and 80 for the IdP server.

### 2.2.1 Set the IdP hostname

```
vim /etc/hosts
```

```
<YOUR SERVER IP ADDRESS> idp.example.org <HOSTNAME>
```

```
hostnamectl set-hostname <HOSTNAME>
```

(Replace idp.example.org with your IdP Full Qualified Domain Name and <HOSTNAME> with the IdP hostname)

### 2.2.2 Set the variable JAVA\_HOME in /etc/environment

Set JAVA\_HOME:

```
# vim /etc/environment → Y écrire : JAVA_HOME=/usr/lib/jvm/java-11-amazon-corretto
```

```
# source /etc/environment
```

```
# export JAVA_HOME=/usr/lib/jvm/java-11-amazon-corretto
```

```
# echo $JAVA_HOME
```

## 2.3 Install Shibboleth Identity Provider v4.x

The Identity Provider (IdP) is responsible for user authentication and providing user information to the Service Provider (SP). It is located at the home organization, which is the organization which maintains the user's account. It is a Java Web Application that can be deployed with its WAR file.

- Download the Shibboleth Identity Provider v4.x.y (replace '4.x.y' with the latest version found [here](#)):

```
# cd /usr/local/src
```

```
# wget https://shibboleth.net/downloads/identity-provider/4.1.2/shibboleth-identity-provider-4.1.2.tar.gz
```

```
# tar -xzf shibboleth-identity-provider-4.1.2.tar.gz
```

- Run the installer install.sh:

According to [NSA and NIST](#), RSA with 3072 bit-modulus is the minimum to protect up to TOP SECRET over than 2030.

```
# cd /usr/local/src/shibboleth-identity-provider-4.1.2/bin
```

```
# bash install.sh -Didp.host.name=$(hostname -f) -Didp.keysize=3072
```

```
Buildfile: /usr/local/src/shibboleth-identity-provider-4.x.y/bin/build.xml
```

```
install:
```

```
Source (Distribution) Directory (press <enter> to accept default): [/usr/local/src/shibboleth-identity-provider-4.x.y] ?
```

```
Installation Directory: [/opt/shibboleth-idp] ? [ENTER]
```

Backchannel PKCS12 Password: ###PASSWORD-FOR-BACKCHANNEL###

Re-enter password: ###PASSWORD-FOR-BACKCHANNEL###

Cookie Encryption Key Password: ###PASSWORD-FOR-COOKIE-ENCRYPTION###

Re-enter password: ###PASSWORD-FOR-COOKIE-ENCRYPTION###

SAML EntityID: [<https://idp.example.org/idp/shibboleth>] ?

Attribute Scope: [example.org] ?

By starting from this point, the variable `idp.home` refers to the directory: `/opt/shibboleth-idp`  
Backup the `###PASSWORD-FOR-BACKCHANNEL###` value somewhere to be able to find it when you need it.

The `###PASSWORD-FOR-COOKIE-ENCRYPTION###` will be saved into `/opt/shibboleth-idp/credentials/secrets.properties` as `idp.sealer.storePassword` and `idp.sealer.keyPassword` value.

## 2.4 Install Jetty 9 Web Server

Jetty is a Web server and a Java Servlet container. It will be used to run the IdP application through its WAR file.

### 2.4.1 Installation

1. Download and Extract Jetty

```
# cd /usr/local/src
```

```
# wget https://repo1.maven.org/maven2/org/eclipse/jetty/jetty-distribution/9.4.42.v20210604/jetty-distribution-9.4.42.v20210604.tar.gz
```

```
# tar xzvf jetty-distribution-9.4.42.v20210604.tar.gz
```

2. Create the `jetty-src` folder as a symbolic link. It will be useful for future Jetty updates:

```
# ln -nsf jetty-distribution-9.4.42.v20210604 jetty-src
```

3. Create the system user `jetty` that can run the web server (without home directory):

```
# useradd -r -M jetty
```

4. Create your custom Jetty configuration that overrides the default one and will survive upgrades:

```
# mkdir /opt/jetty
```

```
# wget https://registry.idem.garr.it/idem-conf/shibboleth/IDP4/jetty/start.ini -O /opt/jetty/start.ini
```

5. Create the `TMPDIR` directory used by Jetty:

```
# mkdir /opt/jetty/tmp ; chown jetty:jetty /opt/jetty/tmp
```

```
# chown -R jetty:jetty /opt/jetty /usr/local/src/jetty-src
```

6. Create the Jetty Log's folder:

```
# mkdir /var/log/jetty
```

```
# mkdir /opt/jetty/logs
```

```
# chown jetty:jetty /var/log/jetty /opt/jetty/logs
```

7. Configure /etc/default/jetty:

```
# vim /etc/default/jetty
```

Contenu à insérer :

```
JETTY_HOME=/usr/local/src/jetty-src  
JETTY_BASE=/opt/jetty  
JETTY_USER=jetty  
JETTY_START_LOG=/var/log/jetty/start.log  
TMPDIR=/opt/jetty/tmp
```

8. Create the service loadable from command line:

```
# cd /etc/init.d
```

```
# ln -s /usr/local/src/jetty-src/bin/jetty.sh jetty
```

```
# update-rc.d jetty defaults
```

9. Check if all settings are OK:

```
# service jetty check (Jetty NOT running)
```

```
# service jetty start
```

```
# service jetty check (Jetty running pid=XXXX)
```

If you receive an error likes "Job for jetty.service failed because the control process exited with error code. See "systemctl status jetty.service" and "journalctl -xe" for details.",

try this:

```
# rm /var/run/jetty.pid
```

```
# systemctl start jetty.service
```

## 2.5 Configuration Instructions

### 2.5.1 Configure Jetty

- o Configure the IdP Context Descriptor:

```
# mkdir /opt/jetty/webapps
```

```
# vim /opt/jetty/webapps/idp.xml
```

Contenu à insérer

```
<Configure class="org.eclipse.jetty.webapp.WebAppContext">  
<Set name="war"><SystemProperty name="idp.home"/>/war/idp.war</Set>  
<Set name="contextPath">/idp</Set>  
<Set name="extractWAR">>false</Set>  
<Set name="copyWebDir">>false</Set>  
<Set name="copyWebInf">>true</Set>  
<Set name="persistTempDirectory">>false</Set>  
</Configure>
```

- o Make the jetty user owner of IdP main directories:

```
# cd /opt/shibboleth-idp
```

```
# chown -R jetty logs/ metadata/ credentials/ conf/ war/
```

- o Restart Jetty:

```
# systemctl restart jetty.service
```

### 2.5.2 Configure SSL on Apache2 (front-end of Jetty)

The Apache HTTP Server will be configured as a reverse proxy and it will be used for SSL offloading.

- o Create the DocumentRoot:

```
# mkdir /var/www/html/${hostname -f}
```

```
# sudo chown -R www-data: /var/www/html/${hostname -f}
```

```
# echo '<h1>It Works!</h1>' > /var/www/html/${hostname -f}/index.html
```

- o Create the Virtualhost file (please pay attention: you need to edit this file and customize it, check the initial comment inside of it):

```
# wget
```

```
https://registry.idem.garr.it/idem-conf/shibboleth/IDP4/apache2/idp.example.org.conf -O  
/etc/apache2/sites-available/${hostname -f}.conf
```

- o Configure the right privileges for the SSL Certificate and Key used by HTTPS:

```
# chmod 400 /etc/apache2/certs/$(hostname -f).key
```

```
# chmod 644 /etc/apache2/certs/$(hostname -f).crt
```

\$(hostname -f) will provide your IdP Full Qualified Domain Name)

- o Enable the required Apache2 modules and the virtual hosts:

```
# a2enmod proxy_http ssl headers alias include negotiation
```

```
# a2ensite $(hostname -f).conf
```

```
# a2dissite 000-default.conf default-ssl
```

```
# systemctl restart apache2.service
```

- o Check that IdP metadata is available on:

- o <https://idp.yourdomain.be/idp/shibboleth>

- o Verify the strength of your IdP's machine on:

- o <https://www.ssllabs.com/ssltest/analyze.html>

### 3 Configure Shibboleth Identity Provider Storage

- Shibboleth Documentation

Reference: <https://wiki.shibboleth.net/confluence/display/IDP4/StorageConfiguration>

The IdP provides a number of general-purpose storage facilities that can be used by core subsystems like session management and consent.

#### **Stratégie utilisée : HTML Local Storage, Encryption GCM, No Database**

The HTML Local Storage requires JavaScript be enabled because reading and writing to the client requires an explicit page be rendered. Note that this feature is safe to enable globally. The implementation is written to check for this capability in each client, and to back off to cookies. The default configuration generates encrypted assertions that a large percentage of non-Shibboleth SPs are going to be unable to decrypt, resulting a wide variety of failures and error messages. Some old Shibboleth SPs or software running on old Operating Systems will also fail to work.

If you don't change anything, the IdP stores data in a browser session cookie or HTML local storage and encrypt his assertions with AES-GCM encryption algorithm.

The IDEM Federation Operators collect a list of Service Providers that don't support the new default encryption algorithm and provide a solution [here](#) (Italian only).

See the configuration files and the Shibboleth documentation for details.



Check IdP Status:

- `bash /opt/shibboleth-idp/bin/status.sh`

## 4 Configuration de Shibboleth

### 4.1 Configuration des metadatas

- Configurer le fichier `/opt/shibboleth/metadata/idp-metadata.xml`

**ATTENTION** : Il faut supprimer la date `validUntil="2021-06-30T12:15:34.029Z"` dans le bloc suivant

```
<EntityDescriptor xmlns="urn:oasis:names:tc:SAML:2.0:metadata"
xmlns:ds="http://www.w3.org/2000/09/xmldsig#"
xmlns:shibmd="urn:mace:shibboleth:metadata:1.0"
xmlns:xml="http://www.w3.org/XML/1998/namespace"
xmlns:mdui="urn:oasis:names:tc:SAML:metadata:ui"
xmlns:mdrpi="urn:oasis:names:tc:SAML:metadata:rpi" xmlns:req-
attr="urn:oasis:names:tc:SAML:protocol:ext:req-attr" validUntil="2021-06-30T12:15:34.029Z"
entityID="https://idp.yourdomain.be/idp/shibboleth">
```

### 4.2 Installer les certificats Belnet et eduGain

the setup requires that you have Belnet Federation's certificate to validate the signature of the published metadata ; to get it, issue following command :

#### 4.2.1 Certificat BELNET

**Méthode 1 :**

```
# wget https://federation.belnet.be/certificate.federation.belnet.be.pem -O
/opt/shibboleth-idp/conf/credentials/certificate.federation.belnet.be.crt
```

**Méthode 2 :**

Si indispo, reprendre sur un ancien IDP dans `/opt/shibboleth/credentials/` ou dans les fichiers qui accompagnent cette procédure.

Ce certif n'est pas renouvelé automatiquement. Seulement si BELNET nous prévient

#### 4.2.2 Certificat eduGain

**Méthode 1 :**

<https://www.edugain.org/mds-2014.cer>

**Méthode 2 :**

Si indispo, reprendre sur un ancien IDP dans /opt/shibboleth/credentials/ ou dans les fichiers qui accompagnent cette procédure.

Ce certif n'est pas renouvelé automatiquement. Seulement si eduGain ou BELNET nous informe(nt)

### 4.3 Configurer les « metadata providers »

Editer le fichier /opt/shibboleth/metadata-providers.xml

Ce fichier permet de déclarer les fournisseurs de metadata avec lesquels nous travaillons mais aussi de télécharger une copie locale

**Remarque :** Ce fichier a été créé à partir des documentations officielles de BELNET et d'edugain et

**Contenu :**

```
<?xml version="1.0" encoding="UTF-8"?>
<MetadataProvider id="ShibbolethMetadata" xsi:type="ChainingMetadataProvider"
  xmlns="urn:mace:shibboleth:2.0:metadata"
  xmlns:security="urn:mace:shibboleth:2.0:security"
  xmlns:saml="urn:oasis:names:tc:SAML:2.0:assertion"
  xmlns:md="urn:oasis:names:tc:SAML:2.0:metadata"
  xmlns:alg="urn:oasis:names:tc:SAML:metadata:algsupport"
  xmlns:ds="http://www.w3.org/2000/09/xmldsig#"
  xmlns:ds11="http://www.w3.org/2009/xmldsig11#"
  xmlns:enc="http://www.w3.org/2001/04/xmlenc#"
  xmlns:enc11="http://www.w3.org/2009/xmlenc11#"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="urn:mace:shibboleth:2.0:metadata
http://shibboleth.net/schema/idp/shibboleth-metadata.xsd
          urn:mace:shibboleth:2.0:security http://shibboleth.net/schema/idp/shibboleth-
security.xsd
          urn:oasis:names:tc:SAML:2.0:assertion
http://docs.oasis-open.org/security/saml/v2.0/saml-schema-assertion-2.0.xsd
          urn:oasis:names:tc:SAML:2.0:metadata
http://docs.oasis-open.org/security/saml/v2.0/saml-schema-metadata-2.0.xsd
```

```

urn:oasis:names:tc:SAML:metadata:algsupport
http://docs.oasis-open.org/security/saml/Post2.0/sstc-saml-metadata-algsupport-v1.0.xsd

http://www.w3.org/2000/09/xmlsig# http://www.w3.org/TR/2002/REC-xmlsig-
core-20020212/xmlsig-core-schema.xsd

http://www.w3.org/2009/xmlsig11# http://www.w3.org/TR/2013/REC-xmlsig-
core1-20130411/xmlsig11-schema.xsd

http://www.w3.org/2001/04/xmlenc# http://www.w3.org/TR/xmlenc-core/xenc-
schema.xsd

http://www.w3.org/2009/xmlenc11# http://www.w3.org/TR/2013/REC-xmlenc-
core1-20130411/xenc-schema-11.xsd"

sortKey="1">

<!-- ***** Belnet Federation ***** -->

<MetadataProvider id="URLMD"

    xsi:type="FileBackedHTTPMetadataProvider"

    backingFile="%{idp.home}/metadata/belnet-refed-metadata.xml"

    metadataURL="https://federation.belnet.be/metadata/re/metadata.xml">

<MetadataFilter xsi:type="SignatureValidation"

    certificateFile="%{idp.home}/credentials/certificate.federation.belnet.be.pem"

    requireSignedRoot="false">

</MetadataFilter>

<MetadataFilter xsi:type="EntityRole">

    <RetainedRole>md:SPSSODescriptor</RetainedRole>

</MetadataFilter>

</MetadataProvider>

<!-- ***** eduGAIN Federation ***** -->

```

```
<MetadataProvider id="URLMD4" xsi:type="FileBackedHTTPMetadataProvider"
```

```
xmlns="urn:mace:shibboleth:2.0:metadata"
```

```
metadataURL="http://mds.edugain.org"
```

```
backingFile="%{idp.home}/metadata/mds.edugain.org.xml" >
```

```
    <MetadataFilter xsi:type="SignatureValidation"
```

```
        certificateFile="${idp.home}/credentials/edugain-mds-2014.cer"
```

```
        requireSignedRoot="false">
```

```
    </MetadataFilter>
```

```
    <MetadataFilter xsi:type="EntityRole">
```

```
        <RetainedRole>md:SPSSODescriptor</RetainedRole>
```

```
    </MetadataFilter>
```

```
</MetadataProvider>
```

```
<!-- ***** Azure AD ***** -->
```

```
<MetadataProvider id="AzureAD-idp-metadata"
```

```
    xsi:type="FilesystemMetadataProvider"
```

```
    metadataFile="/opt/shibboleth-idp/metadata/AzureAD-idp.xml" />
```

## 5 Using SAML Proxying in the Shibboleth IdP to connect with Azure AD

A [French version of this document](#) can be found on the CANARIE website.

Please read and follow the [documentation](#) first, before or along with using this example. This documentation is not maintained by the development team and may not be entirely accurate or consistent with the software at any given time. It is a complement to the documentation, not a replacement for it.

### 5.1 Overview

This configuration recipe of the Shibboleth IdP leverages the SAML proxying features such that Azure AD can be used for sign-in while Shibboleth handles the features many R&E federation's trust models value. Using this approach uses just the IdP as a SAML proxy without the necessity of extra elements.

### 5.2 IdP Proxying: Appearances and Perspectives

Proxying techniques are confusing at times and it is helpful to understand the approach and your perspective:

#### Azure ADs:

- Shibboleth V4 IdP will look like a Relying Party to Azure AD
- It will be a **single** non-Gallery App registered in the Enterprise Apps portal for Azure
- means that all conditional access and policy rules are applied at an IdP-wide level, **NOT** per Shibboleth Relying Party.
- also means that applying rules for MFA *as controlled by Azure AD* are for the entire IdP and NOT discrete Shibboleth Relying Parties.

#### Relying Party (Service Provider) from the multi-lateral trust/R&E federation community:

- It will look like a fully functional multi-lateral capable IdP
- It will not require any changes in behaviour to the SP
- Attribute asserted over the wire are what the SP expects. i.e. attributes are NOT seen as 'claims'

#### Users:

- A user will sign into Azure AD
- The Shibboleth IdP as proxy will redirect as necessary
- The user will have two sessions:
  - one with Azure AD
  - one with the Shibboleth IdP

#### Federation Operator:

- The entity registered in the R&E federation is the Shibboleth IdP, built for and by the R&E community and should meet all technical requirements as does any other Shibboleth IdP
- Alignment to any federation baseline expectations is not just software but also how it's operated and managed and is in the hands of the IdP operator like any other IdP.

## IdP Proxying: What a Proxy Flow Looks Like

When the user initiates sign-on the following usually happens:

1. An Authentication request arrives at Shibboleth IdP
2. The Shibboleth IdP observes it's configured for SAML sign on and redirects to an upstream IdP (Azure AD). Settings for this are controlled in
3. `idp.properties`
4. `authn/saml-authn-config.xml`
5. User Authenticates or has an existing session at upstream IdP (Azure AD)
6. The upstream IdP (Azure AD) constructs a SAML Assertion with one or more attributes and is sent with the user to the Shibboleth IdP
7. The Shibboleth IdP receives the assertion and:
8. verifies that the assertion arrives from an entity it trusts as configured in `metadata-providers.xml`
9. filters the assertion according to rules in `attribute-filter.xml`
10. Extracts the real user as configured in [attribute-based subject c14n](#).
11. Looks through list of `AttributesToResolve` in the resolver and resolves each one.
12. Looks through list of resulting attributes in `AttributeSourceIds` and picks the first valid one to be the principal's name to be used later
13. Resulting trusted *real* username is used as `$resolutionContext.principal` (eg. existing LDAP data connector, etc.) during "standard" attribute resolution process

## 5.3 Implementing the Solution

### 5.3.1 Prerequisites

Be sure to have these assets in place and appropriate access to them before you start:

14. A working Shibboleth Identity Provider at V4 or above running somewhere.
15. An active Azure AD tenant that you have administrative control in
16. The ability in Azure AD to create an enterprise Non-Gallery SAML App
17. A suitable attribute available to both IdPs to use as a "joining" attribute used in local lookups if necessary.

### 5.3.2 Terms and Settings

This document refers to some key settings and terms described here. For your installation have these on hand to speed up configuration:

- **Your original IdP EntityID:** <https://idp.example.com/idp>
- **Your Upstream IdP EntityID which is Azure AD Identifier:** [https://sts.windows.net/<sts\\_tenant\\_id>](https://sts.windows.net/<sts_tenant_id>)
- `sts_tenant_id` can be found most easily by creating a relying party in Azure AD to work with:
- sign into the Azure AD Portal -> choose Enterprise Applications -> Create New Application > Non Gallery Application → Actually create one → select SAML Sign On -> select SAML Sign On settings
- Section 4 contains the Azure AD Identifier which *includes the trailing slash*
- The Proxy Joining attribute common to both services:
- `SamAccountName` is often a good choice and appears as 'name' in claims.
- will exist as a 'scoped' username

- the scope being that of the domain used on-premises and is usually internet friendly (not something.local or something.int)
- **Relying Party/Service Provider** Microsoft will use "Relying Party" at times to mean "Service Provider"

## 5.4 Steps and Tasks

### 5.4.1 Trust Task: 1. Update your IdP's metadata

As your IdP will need act as an SP, you'll need extra blocks in your entity's metadata.

- Update your existing idp-metadata.xml file to include a <SPSSODescriptor> block.
- Copy the signing and encryption certificates from the IdP part of the metadata and replace the base URI used below as an example (<https://idp.example.com/idp>) with the base of your IdP.

This SPSSODescriptor enriched metadata is used with your upstream IDP (Azure AD)

**ATTENTION** : Ajouter le bloc **SPSSODescriptor** avant IDPSSODescriptor

```
<EntityDescriptor entityID=" https://idp.example.com/idp" ...>
<!-- New SP block -->
  <SPSSODescriptor protocolSupportEnumeration="urn:oasis:names:tc:SAML:2.0:protocol">
    <KeyDescriptor use="signing">
      <ds:KeyInfo>
        <ds:X509Data>
          <ds:X509Certificate>
            ...Signing Certificate from IdP...
          </ds:X509Certificate>
        </ds:X509Data>
      </ds:KeyInfo>
    </KeyDescriptor>
    <KeyDescriptor use="encryption">
      <ds:KeyInfo>
        <ds:X509Data>
          <ds:X509Certificate>
```

```

...Encryption Certificate from IdP...

</ds:X509Certificate>

</ds:X509Data>

</ds:KeyInfo>

</KeyDescriptor>

<AssertionConsumerService Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST" Location="
https://idp.example.com/idp/profile/Authn/SAML2/POST/SSO" index="0"/>

</SPSSODescriptor>

<!-- Already present IdP data -->

<IDPSSODescriptor ...>

...

</IDPSSODescriptor>

<AttributeAuthorityDescriptor>

...

</AttributeAuthorityDescriptor>

</EntityDescriptor>

```

#### 5.4.2 Envoyer le fichier idp-metadata.xml à Belnet

A cette étape on peut déjà envoyer les metadatas à Belnet via l'interface graphique <https://federation.belnet.be/> (ou <https://federation.belnet.be/md-mgmt/apply/>)

#### 5.4.3 Trust Task: 2. Register your IdP with Azure AD

An Azure AD Enterprise Application needs to be created of type 'Non-Gallery Application' and configured for SAML.

##### Steps to create the app:

- sign in to the Azure AD Portal > choose Enterprise Applications > Create New Application > Non Gallery Application > Actually create one > select SAML Sign On > select SAML Sign On settings




Once created edit the Basic SAML Configuration Section where you will use two things:

- the EntityID: <https://idp.example.com/idp/shibboleth> (same as for your IdP )
- the Assertion Consumer Service (ACS)  
URL: <https://idp.example.com/idp/profile/Authn/SAML2/POST/SSO>

Other items like Logout URL can also be provided but the Shibboleth side will not handle logout in this case, so this is best omitted.


### Basic SAML Configuration

 Save

---


Identifier (Entity ID) \* ⓘ  
The default identifier will be the audience of the SAML response for IDP-initiated SSO

Default

✓  ⓘ 

Reply URL (Assertion Consumer Service URL) \* ⓘ  
The default reply URL will be the destination in the SAML response for IDP-initiated SSO

Default

✓  ⓘ 

Sign on URL ⓘ

Relay State ⓘ

Logout Url ⓘ

Keep this Relying Party editing environment open for the next step.

## 5.4.4 Trust Task: 3. Register the upstream IdP's metadata locally

### 5.4.4.1 Ajout du lien vers le metadata dans metadata-providers.xml

Your Shibboleth IdP doesn't know of the Azure AD IdP so you need to register it locally. This is handled just like any other metadata and can be included in your **metadata-providers.xml** as a new <MetadataProvider> element. For example:

```
<MetadataProvider id="AzureAD-idp-metadata"  
  xsi:type="FilesystemMetadataProvider"  
  metadataFile="/opt/idp/metadata/AzureAD-idp.xml" />
```

#### 5.4.4.2 Récupération du fichier metadata sur le portail Azure

Le fichier XML Metadata doit être téléchargé sur le portail Azure et renommé `AzureAD-idp.xml` une fois uploadé dans `/metadatadata`

##### Informations à vérifier :

The file `AzureAD-idp.xml` must contain valid SAML 2. Metadata for your tenant's entity containing:

- an IDPSSODescriptor block containing a hand entered `shibmd:scope` element
- an X509Descriptor element with `use=signing`
- 2 SingleSignOnService elements
- 1 SingleLogout element (not really supported but will allow error responses to be returned to Azure)

This can be most easily found and downloaded by clicking on '**Federation Metadata XML Download**' in Section 3 of the Azure AD Relying Party information, however it needs to be scrubbed a bit to produce a lean version of the metadata.

Hint: Those on mac or unix may find it convenient processing the file through `xmllint --format downloadedfile.xml > downloadedfile-formated.xml`

(xmllint can be found in a package named `libxml2` on RedHat or `libxml2-utils` on Debian/Ubuntu.)

Hand-adjust the downloaded metadata to add both the XML NameSpace and a value for `shibmd:Scope` in the IDPSSODescriptor element:

- TODO : Ajout dans la balise "EntityDescriptor" de l'élément suivant :  
`xmlns:shibmd="urn:mace:shibboleth:metadata:1.0"`
- add the Extensions element inside the IDPSSODescriptor element to align with the scope validation per the rule in **Proxy Task 2** below:

```
<Extensions>
<shibmd:Scope regexp="false">yourdomain</shibmd:Scope>
</Extensions>
```

When done, add an entry to `metadata-providers.xml`. If you fetch this entry elsewhere or by other means (e.g. curl or otherwise) ensure you know and understand its pedigree and don't blindly trust it without some diligence of some sort.

## SAML Signing Certificate

Status	Active
Thumbprint	36740CBA6
Expiration	8/21/2023,
Notification Email	azadmin@c
App Federation Metadata Url	<a href="https://loc">https://loc</a>
Certificate (Base64)	<a href="#">Download</a>
Certificate (Raw)	<a href="#">Download</a>
Federation Metadata XML	<a href="#">Download</a>

- About certificates:

The certificate generated by Azure AD is only 3 years in duration and is the trust between Azure and the Shibboleth Proxy only. --> On sera prévenus par mail, il faudra rééditer le fichier avant de l'uploader dans les metadatas

- Expect Azure AD to cease trust when it expires.
- Also expect certificate rollover between Azure AD and your IdP instance to be handled by the IdP admin team.
- About the metadata download itself:
- There are no linefeeds between lines (so reformat e.g. with xmllint as shown above, if desired)
- It contains unnecessary elements that can be removed to reduce the size of the file:
- a signature embedded in the top of the file
- The section Fed:ClaimTypesOffered

### 5.4.4.3 Trust Task: 4. Configure Azure AD Attribute Release to the Shibboleth IdP

While still in the edit mode of the Relying Party, configure the necessary attributes needed for the Shibboleth IdP operation.

- For a pass-through proxy approach
- All attributes originate from Azure AD and must be released to this Relying Party for the Shibboleth IdP to marshal downstream
- For a hybrid proxy approach
- Technically the single attribute you want to use for user lookup is required.

2

User Attributes & Claims		Edit
givenname	user.givenname	
surname	user.surname	
emailaddress	user.mail	
name	user.userprincipalname	
Unique User Identifier	user.userprincipalname	
Group	user.groups	

user.userprincipalname is the usual choice for the main user identifier but review your practices carefully around its use and potential re-use. This is going to be especially critical around MFA and assurance attestations to ensure they have a unique identifier that is unchanging.

## 5.5 Configure the IdP for Proxing Behaviour

The following changes are needed to adjust the IdP to proxying behaviour:

- Changing the authentication flow to SAML authentication
- Configuring which Entity to delegate to for the flow
- Update attribute filter to allow incoming attributes to be ingested
- Set up attribute extraction through Subject Canonicalisation (c14n and resolver)

### 5.5.1 Proxy Task 1. Change the IdP authentication flow to SAML

There are three steps for this task:

1. **Edit *authn/authn-comparison.xml* (différent de la procédure originale) to set the EntityID of the Azure AD Entity:**

Uncomment the **shibboleth.authn.SAML.discoveryFunction** bean and edit the target:

REPLACE sts\_tenant\_id with your identifier. **NOTE THE TRAILING SLASH IS TO BE INCLUDED**

```
<bean id="shibboleth.authn.SAML.discoveryFunction" parent="shibboleth.Functions.Constant"
  c:target="https://sts.windows.net/<sts_tenant_id>/" />
```

2. **Enable the flow by updating** idp.authn.flows in *idp.properties* to set it to SAML:

```
idp.authn.flows=SAML
```

Avec Shib 4.1, il est nécessaire de décommenter et updatere les lignes suivantes dans le fichier *authn.properties* :

```
idp.authn.SAML.proxyEntityID = https://sts.windows.net/<sts_tenant_id>/
```

```
idp.authn.SAML.discoveryRequired = true
```

## 5.5.2 Proxy Task 2. Update Your Attribute Filter

The IdP will not ingest attributes from the Azure AD Upstream IdP unless they're allowed in by a filter.

1. Add a new <AttributeFilterPolicy> to permit trusted attributes to be handled.
2. REPLACE sts\_tenant\_id with your identifier. **NOTE THE TRAILING SLASH TO BE INCLUDED**

**Note:** There is a policy rule ScopeMatchesShibMDScope in effect on the attribute 'name' (known internally as azureName).

This will enforce that the idp.scope set in conf/idp.properties agrees with the Azure AD field to avoid any oddities. If they disagree, this rule will fail-closed and not sign a user.

Be sure the IdP metadata for the your Azure AD IdP has the right scope for things to work smoothly

```
<AttributeFilterPolicy id="FilterPolicyObject-Proxy-FromAzure-byIssuer-Type">
  <PolicyRequirementRule xsi:type="Issuer" value="https://sts.windows.net/<sts_tenant_id>/" />
  <AttributeRule attributeID="azureDisplayname" permitAny="true" />
  <AttributeRule attributeID="azureGivenname" permitAny="true" />
  <AttributeRule attributeID="azureSurname" permitAny="true" />
  <AttributeRule attributeID="azureAuthnmethodsreferences" permitAny="true" />
  <AttributeRule attributeID="azureIdentityprovider" permitAny="true" />
  <AttributeRule attributeID="azureTenantid" permitAny="true" />
  <AttributeRule attributeID="azureEmailaddress" permitAny="true" />
  <AttributeRule attributeID="azureObjectidentifier" permitAny="true" />
  <AttributeRule attributeID="azureName">
    <PermitValueRule xsi:type="ScopeMatchesShibMDScope" />
  </AttributeRule>
</AttributeFilterPolicy>
```

## 5.5.3 Proxy Task 3. Enable IdP to Recognize Azure AD Claims

Azure AD issues SAML assertions, however they are presented in an Azure/WS-Fed-centric naming convention (as "claims").

Our technique is to add in a new attribute mapping file that we can then use to parse the claims into internal attributes and in turn use them in the attribute resolver.

- **Add** a new file called in the IdP as *attributes/azureClaims.xml* if it doesn't already exist. This file contains each of your attributes from Azure AD that you want to use in the resolver.

The sample below is not exhaustive but has enough to get started on the claims file.

- For azureName we apply a scoped rule for safety considerations. The scope value MUST match the <shibmd:Scope> extension in the upstream IdP metadata.
- The "saml2.nameFormat" rule property is urn:oasis:names:tc:SAML:2.0:attrname-format:unspecified as the claims don't carry the proper format on them.

```
<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
  xmlns:context="http://www.springframework.org/schema/context"
  xmlns:util="http://www.springframework.org/schema/util"
  xmlns:p="http://www.springframework.org/schema/p"
  xmlns:c="http://www.springframework.org/schema/c"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://www.springframework.org/schema/beans
http://www.springframework.org/schema/beans/spring-beans.xsd
http://www.springframework.org/schema/context
http://www.springframework.org/schema/context/spring-context.xsd
http://www.springframework.org/schema/util
http://www.springframework.org/schema/util/spring-util.xsd"
  default-init-method="initialize"
  default-destroy-method="destroy">
<bean parent="shibboleth.TranscodingRuleLoader">
<constructor-arg>
<list>
  <!-- claims relevant to person record -->
<bean parent="shibboleth.TranscodingProperties">
```

```

<property name="properties">
  <props merge="true">
    <prop key="id">azureName</prop>
    <prop key="transcoder">SAML2ScopedStringTranscoder</prop>
    <prop key="saml2.name">
http://schemas.xmlsoap.org/ws/2005/05/identity/claims/name</prop>
    <prop key="saml2.nameFormat">urn:oasis:names:tc:SAML:2.0:attrname-format:unspecified</prop>
    <prop key="displayName.en">Name</prop>
    <prop key="description.en">Azure UPN of an account expected to be scoped thus transcoded that way</prop>
  </props>
</property>
</bean>
<bean parent="shibboleth.TranscodingProperties">
  <property name="properties">
    <props merge="true">
      <prop key="id">azureEmailaddress</prop>
      <prop key="transcoder">SAML2StringTranscoder</prop>
      <prop key="saml2.name">
http://schemas.xmlsoap.org/ws/2005/05/identity/claims/emailaddress</prop>
      <prop key="saml2.nameFormat">urn:oasis:names:tc:SAML:2.0:attrname-format:unspecified</prop>
      <prop key="displayName.en">Mail</prop>
      <prop key="description.en">Azure emailaddress field of an account</prop>
    </props>
  </property>
</bean>

```

```

<bean parent="shibboleth.TranscodingProperties">
  <property name="properties">
    <props merge="true">
      <prop key="id">azureDisplayname</prop>
      <prop key="transcoder">SAML2StringTranscoder</prop>
      <prop key="saml2.name">
http://schemas.microsoft.com/identity/claims/displayname</prop>
      <prop key="saml2.nameFormat">urn:oasis:names:tc:SAML:2.0:attrname-
format:unspecified</prop>
      <prop key="displayName.en">Mail</prop>
      <prop key="description.en">Azure displayname field of an account</prop>
    </props>
  </property>
</bean>

<bean parent="shibboleth.TranscodingProperties">
  <property name="properties">
    <props merge="true">
      <prop key="id">azureGivenname</prop>
      <prop key="transcoder">SAML2StringTranscoder</prop>
      <prop key="saml2.name">
http://schemas.xmlsoap.org/ws/2005/05/identity/claims/givenname</prop>
      <prop key="saml2.nameFormat">urn:oasis:names:tc:SAML:2.0:attrname-
format:unspecified</prop>
      <prop key="displayName.en">Given name</prop>
      <prop key="description.en">Azure given name of an account</prop>
    </props>
  </property>
</bean>

```



```

<bean parent="shibboleth.TranscodingProperties">
  <property name="properties">
    <props merge="true">
      <prop key="id">azureSurname</prop>
      <prop key="transcoder">SAML2StringTranscoder</prop>
      <prop key="saml2.name">
http://schemas.xmlsoap.org/ws/2005/05/identity/claims/surname</prop>
      <prop key="saml2.nameFormat">urn:oasis:names:tc:SAML:2.0:attrname-
format:unspecified</prop>
      <prop key="displayName.en">Surname</prop>
      <prop key="description.en">Azure surname of an account</prop>
    </props>
  </property>
</bean>

<!-- default claims from Azure for any entity -->
<bean parent="shibboleth.TranscodingProperties">
  <property name="properties">
    <props merge="true">
      <prop key="id">azureTenantid</prop>
      <prop key="transcoder">SAML2StringTranscoder</prop>
      <prop key="saml2.name"> http://schemas.microsoft.com/identity/claims/tenantid</prop>
      <prop key="saml2.nameFormat">urn:oasis:names:tc:SAML:2.0:attrname-
format:unspecified</prop>
      <prop key="displayName.en">Tenant ID</prop>
      <prop key="description.en">Azure tenantid</prop>
    </props>
  </property>
</bean>

```

```

    </property>

</bean>

<bean parent="shibboleth.TranscodingProperties">

  <property name="properties">

    <props merge="true">

      <prop key="id">azureObjectidentifier</prop>

      <prop key="transcoder">SAML2StringTranscoder</prop>

      <prop key="saml2.name">
http://schemas.microsoft.com/identity/claims/objectidentifier</prop>

      <prop key="saml2.nameFormat">urn:oasis:names:tc:SAML:2.0:attrname-
format:unspecified</prop>

      <prop key="displayName.en">Object Identifier</prop>

      <prop key="description.en">Azure object identifier of an account</prop>

    </props>

  </property>

</bean>

<bean parent="shibboleth.TranscodingProperties">

  <property name="properties">

    <props merge="true">

      <prop key="id">azureIdentityprovider</prop>

      <prop key="transcoder">SAML2StringTranscoder</prop>

      <prop key="saml2.name">
http://schemas.microsoft.com/identity/claims/identityprovider</prop>

      <prop key="saml2.nameFormat">urn:oasis:names:tc:SAML:2.0:attrname-
format:unspecified</prop>

      <prop key="displayName.en">Identity Provider entityid</prop>

      <prop key="description.en">Azure entityID of the tenant in Azure</prop>

    </props>

```

```

    </property>

</bean>

<bean parent="shibboleth.TranscodingProperties">

  <property name="properties">

    <props merge="true">

      <prop key="id">azureAuthnmethodsreferences</prop>

      <prop key="transcoder">SAML2StringTranscoder</prop>

      <prop key="saml2.name">
http://schemas.microsoft.com/claims/authnmethodsreferences</prop>

      <prop key="saml2.nameFormat">urn:oasis:names:tc:SAML:2.0:attrname-
format:unspecified</prop>

      <prop key="displayName.en">Authnmethodsreferences</prop>

      <prop key="description.en">Azure authentication method (password, modern auth?
etc)</prop>

    </props>

  </property>

</bean>

</list>

</constructor-arg>

</bean>

</beans>

```

2. Update *attributes/default-rules.xml* to include this new file as a reference by adding this line to it after the last import:

```
<import resource="azureClaims.xml" />
```

3. Update *attribute-resolver.xml* to reveal our new attributes from Azure AD by adding a new DataConnector:

```
<DataConnector id="passthroughAttributes" xsi:type="Subject"
exportAttributes="azureName azureEmailaddress azureDisplayname azureGivenname azureSurname
azureTenantid azureObjectidentifier azureIdentityprovider azureAuthmethodsreferences" />
```

Now that we have the the IdP able to interpret claims from Azure AD, we need to turn our attention to using them for user canonicalization and for populating our attributes.

#### 5.5.4 Proxy Task 4. Subject Canonicalisation

This workflow takes the incoming assertion and extracts some data from it to work out the canonical (authoritative/normalized) username of the user logging in from Azure.

For AzureAD we are going to use the attribute claim: <http://schemas.xmlsoap.org/ws/2005/05/identity/claims/name> which we just mapped internally in the IdP to azName

1. Add a new <AttributeDefinition> to *attribute-resolver.xml* as shown below.

This will transform the azName attribute from the Subject (the filtered data from the incoming assertion) into canonicalNameToUseForJoin attribute for use elsewhere:

```
<AttributeDefinition xsi:type="SubjectDerivedAttribute"
forCanonicalization="true"
id="canonicalNameToUseForJoin"
principalAttributeName="azureName" />
```

2. Now configure which attributes to resolve during c14n:

Define the **shibboleth.c14n.attribute.AttributesToResolve** and **shibboleth.c14n.attribute.AttributeSourceIds** beans in c14n/**subject-c14n.xml** to the attribute ID of the above <AttributeDefinition>:

```
<util:list id="shibboleth.c14n.attribute.AttributesToResolve">
<value>canonicalNameToUseForJoin</value>
</util:list>
<util:list id="shibboleth.c14n.attribute.AttributeSourceIds">
```

```
<value>canonicalNameToUseForJoin</value>
</util:list>
```

**Attention** : dans Shibboleth 4.1, il faut aller dans le fichier `subjectc14n.properties` et éditer ces deux lignes : **Source** : <https://wiki.shibboleth.net/confluence/display/IDP4/AttributePostLoginC14NConfiguration#558042818c1fce692bad4319802ddf4500e90656>

```
idp.c14n.attribute.attributesToResolve = canonicalNameToUseForJoin

# and then select a principal name from

idp.c14n.attribute.attributeSourceIds = canonicalNameToUseForJoin
```

In other proxy situations this may have more than one attribute but for Azure AD we are focused on a single one.

3. Review and ensure the bean in `c14n/subject-c14n.xml` has been uncommented:

```
<bean id="c14n/attribute" parent="shibboleth.PostLoginSubjectCanonicalizationFlow" />
```

At this point you should have a valid, locally understood username to pass into the "normal" resolver that already works, which is now available from places like:

```
$resolutionContext.principal
```

### 5.5.5 Proxy Task 5. Configuring Attribute pass-through and/or hybrid resolving

Attributes originating from Azure AD are referenced in `attribute-resolver.xml` like this:

**Important** : Be sure to comment out the old definition of the names in the `attribute-resolver.xml` or you may get unexpected results.

```
<AttributeDefinition xsi:type="SubjectDerivedAttribute"
  forCanonicalization="false"
  id="mail"
  principalAttributeName="azureEmailAddress" />

<AttributeDefinition xsi:type="SubjectDerivedAttribute"
  forCanonicalization="false"
```

```
id="displayName"
principalAttributeName="azureDisplayname" />
|
<AttributeDefinition xsi:type="SubjectDerivedAttribute"
id="eduPersonPrincipalName"
principalAttributeName="azureEmailaddress" />
```

### 5.5.6 Proxy Task 6. Handling REFEDS AuthnContext Requests (optional)

NOTE : pas implémenté par le Campus

Azure does not currently have a documented way to influence the behavior of the AuthnContext in their SAML assertions. However, Shibboleth provides the means to translate proxy requests and responses via *authn/authn-comparison.xml*. The example below handles REFEDS MFA requests:

```
<util:map id="shibboleth.PrincipalProxyRequestMappings">
  <entry>
    <key>
      <bean parent="shibboleth.SAML2AuthnContextClassRef"
        c:classRef=" https://refeds.org/profile/mfa" />
    </key>
    <list>
      <bean parent="shibboleth.SAML2AuthnContextClassRef"
        c:classRef=" http://schemas.microsoft.com/claims/multipleauthn" />
    </list>
  </entry>
</util:map>
<util:map id="shibboleth.PrincipalProxyResponseMappings">
  <entry>
    <key>
      <bean parent="shibboleth.SAML2AuthnContextClassRef"
```

```

        c:classRef=" http://schemas.microsoft.com/claims/multipleauthn" />
    </key>
    <list>
        <bean parent="shibboleth.SAML2AuthnContextClassRef"
            c:classRef=" https://refeds.org/profile/mfa" />
    </list>
</entry>
</util:map>

```

Update the support matrix for the SAML authentication flow to understand the REFEDS MFA profile

(for v4.0.1) Update the *authn/SAML* bean in *authn/general-authn.xml* so it understands the REFEDS MFA profile by adding a *supportedPrinciples* property:

authn/general-authn.xml updates

```

<bean id="authn/SAML" parent="shibboleth.AuthenticationFlow"
    p:nonBrowserSupported="false"
    p:passiveAuthenticationSupported="true"
    p:forcedAuthenticationSupported="true"
    p:proxyScopingEnforced="true"
    p:discoveryRequired="true">
    <property name="supportedPrincipals">
        <list>
            <bean parent="shibboleth.SAML2AuthnContextClassRef"
                c:classRef="urn:oasis:names:tc:SAML:2.0:ac:classes>PasswordProtectedTransport" />
            <bean parent="shibboleth.SAML2AuthnContextClassRef"
                c:classRef="urn:oasis:names:tc:SAML:2.0:ac:classes>Password" />
            <bean parent="shibboleth.SAML1AuthenticationMethod"

```

```
        c:method="urn:oasis:names:tc:SAML:1.0:am:password" />

    <bean parent="shibboleth.SAML2AuthnContextClassRef"

        c:classRef=" https://refeds.org/profile/mfa" />

    </list>

</property>

</bean>
```

Changes required in v4.1 may be different and you should look at the *authn.properties* file. More details here: [SAMLAuthnConfiguration](#)

### Testing

Restart your IdP for your changes to take effect. Because this is a SAML proxy configuration it doesn't make sense to use `aacli` since it won't have the required information available to it.

Some sites have a developer account which has a tenant that can test entirely isolated from the production tenant. Alternatively you can create a different Azure AD non-gallery SAML app per IdP – one for production, one for pre-production etc. There's no hard and fast rule on the best way however the developer route is free and provides a great model for isolation between credentials as it's a different cookie domain entirely.

### Related content / Recommended Reading

- Shibboleth related:
- [SAMLAuthnConfiguration](#)
- [attribute-based subject c14n](#)
- Azure AD SSO and SAML Related:
- Configuring SAML SSO:  
<https://docs.microsoft.com/en-us/azure/active-directory/manage-apps/configure-saml-single-sign-on>
- Quickstart series: <https://docs.microsoft.com/en-us/azure/active-directory/manage-apps/view-applications-portal>

## 5.6 Configure Shibboleth Identity Provider to release the persistent NameID

Shibboleth Documentation

reference: <https://wiki.shibboleth.net/confluence/display/IDP4/PersistentNameIDGenerationConfiguration>



SAML 2.0 (but not SAML 1.x) defines a kind of NameID called a "persistent" identifier that every SP receives for the IdP users. This part will teach you how to release the "persistent" identifiers with a database (Stored Mode) or without it (Computed Mode).

By default, a transient NameID will always be released to the Service Provider if the persistent one is not requested.

Strategy A - Computed mode - Default & Recommended

- Become ROOT:
  - o sudo su -
- Enable the generation of the computed persistent-id with:

```
# vim /opt/shibboleth-idp/conf/saml-nameid.properties
```

The *sourceAttribute* MUST be an attribute, or a list of comma-separated attributes, that uniquely identify the subject of the generated persistent-id.

The *sourceAttribute* MUST be Stable, Permanent and Not-reassignable attribute.

# ... other things ...#

# OpenLDAP has the UserID into "uid" attribute

```
idp.persistentId.sourceAttribute = azureName
```

- # Active Directory has the UserID into "sAMAccountName"  
#idp.persistentId.sourceAttribute = sAMAccountName  
# ... other things ...#

# BASE64 will match Shibboleth V2 values, we recommend BASE32 encoding for new installs.

```
idp.persistentId.encoding = BASE32
```

```
idp.persistentId.generator = shibboleth.ComputedPersistentIdGenerator
```

```
# vim /opt/shibboleth-idp/conf/saml-nameid.xml
```

Uncomment the line:

```
<ref bean="shibboleth.SAML2PersistentGenerator" />
```

- o vim /opt/shibboleth-idp/credentials/secrets.properties

```
idp.persistentId.salt = ### result of 'openssl rand -base64 36' ###
```

?

- Restart Jetty to apply the changes:

- o systemctl restart jetty.service

- Check IdP Status:

- o bash /opt/shibboleth-idp/bin/status.sh

## 5.7 Configure Shibboleth Identity Provider to release the eduPersonTargetedID

eduPersonTargetedID is an abstracted version of the SAML V2.0 Name Identifier format of "urn:oasis:names:tc:SAML:2.0:nameid-format:persistent".

**Important** : To be able to follow these steps, you need to have followed the previous steps on "persistent" NameID generation.

### Stratégie utilisée : Computed mode - using the computed persistent NameID

- Check to have the <AttributeDefinition> and the <DataConnector> into the attribute-resolver.xml:

```
# vim /opt/shibboleth-idp/conf/attribute-resolver.xml
```

```
<!-- ...other things ... -->

<!-- AttributeDefinition for eduPersonTargetedID - Computed Mode -->

<AttributeDefinition xsi:type="SAML2NameID"
nameIdFormat="urn:oasis:names:tc:SAML:2.0:nameid-format:persistent"
id="eduPersonTargetedID">
  <InputDataConnector ref="computed" attributeNames="computedId" />
</AttributeDefinition>

<!-- ... other things... -->

<!-- Data Connector for eduPersonTargetedID - Computed Mode -->

<DataConnector id="computed" xsi:type="ComputedId"
generatedAttributeID="computedId"
salt="%{idp.persistentId.salt}"
algorithm="%{idp.persistentId.algorithm:SHA}"
encoding="%{idp.persistentId.encoding:BASE32}">

<InputDataConnector ref="passthroughAttributes" attributeNames="%
{idp.persistentId.sourceAttribute}" />

</DataConnector>
```

- Create the custom eduPersonTargetedID.properties file:

```
# wget https://registry.idem.garr.it/idem-conf/shibboleth/IDP4/attributes/custom/eduPersonTargetedID.properties -O
/opt/shibboleth-idp/conf/attributes/custom/eduPersonTargetedID.properties
```

#### Contenu du fichier :

```
# eduPersonTargetedID

id=eduPersonTargetedID

transcoder=SAML2XMLObjectTranscoder

saml2.name=urn:oid:1.3.6.1.4.1.5923.1.1.1.10
```

```
displayName.en=Opaque per-service identifier eduPersonTargetedID
displayName.fr=Identifiant unique par service eduPersonTargetedID
description.en=Opaque per-service identifier eduPersonTargetedID
description.fr=Identifiant unique par service eduPersonTargetedID
saml1.encodeType=false
```

Restart Jetty to apply the changes:

```
# systemctl restart jetty.service
```

- ❓ Check IdP Status:
  - o bash /opt/shibboleth-idp/bin/status.sh

## 5.8 Releaser les attributs

### 5.8.1 Les attributs récupérés d'Azure AD et mappés directement

#### 5.8.1.1 *eduPersonPrincipalName*

Dans attribute-resolver.xml, ajout de

```
<AttributeDefinition xsi:type="SubjectDerivedAttribute"
id="eduPersonPrincipalName"
principalAttributeName="azureEmailaddress" />
```

Modifier l'encodage dans /opt/shibboleth-idp/conf/attributes/eduPerson.xml

```
<bean parent="shibboleth.TranscodingProperties">
  <property name="properties">
    <props merge="true">
      <prop key="id">eduPersonPrincipalName</prop>
```

```
<!--<prop key="transcoder">SAML2ScopedStringTranscoder SAML1ScopedStringTranscoder
CASScopedStringTranscoder</prop-->

<prop key="transcoder">SAML2StringTranscoder SAML1ScopedStringTranscoder
CASScopedStringTranscoder</prop>
```

### 5.8.1.2 uid

Dans attribute-resolver.xml, ajout de

```
<AttributeDefinition xsi:type="SubjectDerivedAttribute"
  forCanonicalization="false"
  id="uid"
  principalAttributeName="azureEmailaddress" />
```

Ajout du bloc suivant dans attribute-filter.xml

```
<AttributeRule attributeID="uid">
  <PermitValueRule xsi:type="ANY" />
</AttributeRule>
```

### 5.8.1.3 cn

Dans attribute-resolver.xml, ajout de

```
<AttributeDefinition xsi:type="SubjectDerivedAttribute"
  forCanonicalization="false"
  id="cn"
  principalAttributeName="azureDisplayname" />
```

Ajout du bloc suivant dans attribute-filter.xml

```
<AttributeRule attributeID="cn">
  <PermitValueRule xsi:type="ANY" />
</AttributeRule>
```

#### 5.8.1.4 *givenName*

Dans attribute-resolver.xml, ajout de

```
<AttributeDefinition xsi:type="SubjectDerivedAttribute"
  forCanonicalization="false"
  id="givenName"
  principalAttributeName="azureGivenname" />
```

Ajout du bloc suivant dans attribute-filter.xml

```
<AttributeRule attributeID="cn">
  <PermitValueRule xsi:type="ANY" />
</AttributeRule>
```

#### 5.8.1.5 *sn*

Dans attribute-resolver.xml, ajout de

```
<AttributeDefinition xsi:type="SubjectDerivedAttribute"
  forCanonicalization="false"
  id="sn"
  principalAttributeName="azureSurname" />
```

Ajout du bloc suivant dans attribute-filter.xml

```
<AttributeRule attributeID="cn">
  <PermitValueRule xsi:type="ANY" />
</AttributeRule>
```

### 5.8.2 Les attributs statiques

#### 5.8.2.1 *o (Organization)*

Dans attribute-resolver.xml, ajout de

```

<DataConnector id="staticAttributeO" xsi:type="Static">

  <Attribute id="o">

    <Value>Your Entreprise</Value>

  </Attribute>

</DataConnector>

<AttributeDefinition id="o" xsi:type="Simple">

  <InputDataConnector ref="staticAttributeO" attributeNames="o" />

</AttributeDefinition>

```

Ajout du bloc suivant dans attribute-filter.xml

```

<AttributeRule attributeID="o">

  <PermitValueRule xsi:type="ANY" />

</AttributeRule>

```

### 5.8.2.2 *preferredLanguage*

Dans attribute-resolver.xml, ajout de

```

<DataConnector id="staticAttributepreferredLanguage" xsi:type="Static">

  <Attribute id="preferredLanguage">

    <Value>FR</Value>

  </Attribute>

</DataConnector>

<AttributeDefinition id="preferredLanguage" xsi:type="Simple">

  <InputDataConnector ref="staticAttributepreferredLanguage"
attributeNames="preferredLanguage" />

</AttributeDefinition>

```

Ajout du bloc suivant dans attribute-filter.xml

```
<AttributeRule attributeID="preferredLanguage">
    <PermitValueRule xsi:type="ANY" />
</AttributeRule>
```

### 5.8.2.3 *StaticSchac*

Dans attribute-resolver.xml, ajout de

```
<!-- staticSchac as Static Attribute -->
<DataConnector id="staticSchac" xsi:type="Static">
<Attribute id="schacHomeOrg">
<Value>yourdomain.be</Value>
</Attribute>
</DataConnector>

<AttributeDefinition id="schacHomeOrg" xsi:type="Simple">
<InputDataConnector ref="staticSchac" attributeNames="schacHomeOrg" />
<AttributeEncoder xsi:type="SAML2String" name="urn:oid:1.3.6.1.4.1.25178.1.2.9"
friendlyName="schacHomeOrganization" />
</AttributeDefinition>
<!-- End of staticSchac as Static Attribute -->
```

Ajout du bloc suivant dans attribute-filter.xml

```
<AttributeRule attributeID="schacHomeOrg">
<PermitValueRule xsi:type="ANY" />
</AttributeRule>
```

### 5.8.2.4 *staticSchacHomeOrganizationType*

Dans attribute-resolver.xml, ajout de

```

<!-- staticSchacHomeOrganizationType as Static Attribute -->

<DataConnector id="staticSchacHomeOrganizationType" xsi:type="Static">

  <Attribute id="schacHomeOrganizationType">

<Value>urn:schac:homeOrganizationType:int:university</Value>

  </Attribute>

</DataConnector>

<AttributeDefinition id="schacHomeOrganizationType" xsi:type="Simple">

<InputDataConnector ref="staticSchacHomeOrganizationType"
attributeNames="schacHomeOrganizationType" />

  <AttributeEncoder xsi:type="SAML2String" name="urn:oid:1.3.6.1.4.1.25178.1.2.10"
friendlyName="schacHomeOrganizationType"/>

  </AttributeDefinition>

<!-- End of staticSchacHomeOrganizationType as Static Attribute -->

```

Ajout du bloc suivant dans attribute-filter.xml

```

<AttributeRule attributeID="staticSchacHomeOrganizationType">

<PermitValueRule xsi:type="ANY" />

</AttributeRule>

```

## 5.8.3 Les attributs mappés

### 5.8.3.1 *belnetEduPersonUniqueID*

Dans attribute-resolver.xml, ajout de

```

<AttributeDefinition id="belnetEduPersonUniqueID" xsi:type="Simple">

<InputDataConnector ref="passthroughAttributes" attributeNames="azureEmailaddress" />

```



```

<DisplayName xml:lang="en">Unique ID</DisplayName>

<DisplayName xml:lang="fr">ID unique</DisplayName>

<DisplayDescription xml:lang="en">Unique ID: A unique identifier for a person, mainly for inter-
institutional user identification.</DisplayDescription>

<DisplayDescription xml:lang="fr">Identifiant unique de l'utilisateur au seins de
l'AAI.</DisplayDescription>

<AttributeEncoder xsi:type="SAML2String" name="urn:oid:2.16.756.1.2.5.1.1.1"
friendlyName="belnetEduPersonUniqueID"/>

</AttributeDefinition>

```

Ajout du bloc suivant dans attribute-filter.xml

```

<AttributeRule attributeID="belnetEduPersonUniqueID">

    <PermitValueRule xsi:type="ANY" />

</AttributeRule>

```

## 5.8.4 Les attributs scriptés sur base d'autres attributs

### 5.8.4.1 *eduPersonScopedAffiliation*

doit avoir la forme eduPersonAffiliation@domain.tld, peut être multi valué

Dans attribute-resolver.xml, ajout de

```

<AttributeDefinition id="eduPersonScopedAffiliation" xsi:type="ScriptedAttribute">

<InputAttributeDefinition ref="eduPersonAffiliation"/>

<Script>

<![CDATA[

if (typeof eduPersonAffiliation != "undefined" && eduPersonAffiliation != null ){

```

```

for ( i = 0; eduPersonAffiliation != null && i < eduPersonAffiliation.getValues().size(); i++ ){

    value = eduPersonAffiliation.getValues().get(i);

eduPersonScopedAffiliation.addValue(value + "@yourdomain.be");

}

}

]]>

</Script>

</AttributeDefinition>

```

Ajout du bloc suivant dans attribute-filter.xml

```

<AttributeRule attributeID="eduPersonScopedAffiliation">

    <PermitValueRule xsi:type="ANY" />

</AttributeRule>

```

Modifier l'encodage dans /opt/shibboleth-idp/conf/attributes/eduPerson.xml

```

<bean parent="shibboleth.TranscodingProperties">

    <property name="properties">

        <props merge="true">

            <prop key="id">eduPersonScopedAffiliation</prop>

            <!--<prop key="transcoder">SAML2ScopedStringTranscoder SAML1ScopedStringTranscoder
CASScopedStringTranscoder</prop-->

            <prop key="transcoder">SAML2StringTranscoder SAML1ScopedStringTranscoder
CASScopedStringTranscoder</prop>

```

### 5.8.4.2 *eduPersonPrimaryAffiliation*

Doit contenir l'affiliation principale de la personne, sa valeur doit obligatoirement être un des valeurs présentes dans eduPersonAffiliation

Dans attribute-resolver.xml, ajout de

```
<AttributeDefinition id="eduPersonPrimaryAffiliation" xsi:type="ScriptedAttribute">
<InputAttributeDefinition ref="eduPersonAffiliation"/>
<Script>
<![CDATA[

if (typeof eduPersonAffiliation != "undefined" && eduPersonAffiliation != null ) {
if ( eduPersonAffiliation.getValues().contains("staff") ) {
eduPersonPrimaryAffiliation.addValue("staff");
}

else if ( eduPersonAffiliation.getValues().contains("student") ) {
eduPersonPrimaryAffiliation.addValue("student");
}
}
}]]>
</Script>
</AttributeDefinition>
```

Ajout du bloc suivant dans attribute-filter.xml

```
<AttributeRule attributeID="eduPersonPrimaryAffiliation">
    <PermitValueRule xsi:type="ANY" />
</AttributeRule>
```

## 5.8.5 Les attributs scriptés/transférés sur base de l'appartenance à des groupes

Ajout d'un nouvel attribut à partir d'Azure AD :

### 5.8.5.1 *eduPersonEntitlement (pas utilisé)*

La technique ci-dessous n'a finalement pas été utilisée à cause de l'impossibilité de relayer plusieurs claims statiques pour un même groupe. Elle reste cependant valable pour relayer un attribut statique unique et personnalisé.

<https://feedback.azure.com/forums/169401-azure-active-directory/suggestions/32988205-support-multivalue-saml-token-attributes>

Dans le portail AzureAD, création d'une nouvelle Claim Statique (sera basée plus tard sur un groupe)

You can also assign any constant (static) value to any claims which you define in Azure AD. Please follow the below steps to assign a constant value:

1. In the [Azure portal](#), on the User Attributes & Claims section, click on the Edit icon to edit the claims.
2. Click on the required claim which you want to modify.
3. Enter the constant value without quotes in the Source attribute as per your organization and click Save.
4. The constant value will be displayed as below.

À partir de l'adresse <<https://docs.microsoft.com/en-us/azure/active-directory/develop/active-directory-saml-claims-customization>>

## Attributs et revendications de l'utilisateur ...

+ Ajouter une nouvelle revendication + Ajouter une revendication de groupe ☰ Colonnes

### Revendication requise

Nom de revendication	Valeur
Identificateur d'utilisateur unique (ID nom)	user.userprincipalname [nameid-1]

### Revendications supplémentaires

Nom de revendication	Valeur
eduPersonEntitlement	"urn:mace:belnet.be:eduvpn:belnet.be:eduPersonEntitlement"
http://schemas.xmlsoap.org/ws/2005/05/identity/claims/emailaddress	user.mail
http://schemas.xmlsoap.org/ws/2005/05/identity/claims/givenname	user.givenname
http://schemas.xmlsoap.org/ws/2005/05/identity/claims/name	user.userprincipalname
http://schemas.xmlsoap.org/ws/2005/05/identity/claims/surname	user.surname

#### 5. Ajout de la revendication dans le fichier \conf\attributes\azureClaims.xml

```
<bean parent="shibboleth.TranscodingProperties">
  <property name="properties">
    <props merge="true">
      <prop key="id">azureeduPersonEntitlement</prop>
      <prop key="transcoder">SAML2StringTranscoder</prop>
      <prop key="saml2.name">eduPersonEntitlement</prop>
      <prop key="saml2.nameFormat">urn:oasis:names:tc:SAML:2.0:attrname-format:unspecified</prop>
      <prop key="displayName.en">eduPersonEntitlement</prop>
      <prop key="description.en">eduPersonEntitlement</prop>
    </props>
  </property>
</bean>
```

```
</props>

</property>

</bean>
```

#### 6. Autoriser dans l'attribut filter : \attribute-filter.xml

Ajout de la ligne suivante : `<AttributeRule attributeID="azureeduPersonEntitlement" permitAny="true" />`

Dans le BLOC

```
<AttributeFilterPolicy id="FilterPolicyObject-Proxy-FromAzure-byIssuer-Type">
```

En dessous de

```
<AttributeRule attributeID="azureObjectidentfier" permitAny="true" />
```

Plus bas dans le fichier, permettre le release habituel de l'attribut transformé :

```
<AttributeRule attributeID="eduPersonEntitlement">

    <PermitValueRule xsi:type="ANY" />

</AttributeRule>
```

#### A. Ajouter la récupération de l'attribut dans attribute-release.xml :

```
<AttributeDefinition xsi:type="SubjectDerivedAttribute"

    forCanonicalization="false"

    id="eduPersonEntitlement"

    principalAttributeName="azureeduPersonEntitlement" />
```

### 5.8.5.2 *eduPersonEntitlement et eduPersonAffiliation*

Technique finalement utilisée pour "eduPersonEntitlement" et "eduPersonAffiliation"

Ces deux attributs seront scriptés sur base de l'appartenance de l'utilisateur à un groupe de sécurité.

#### 1. Récupération des groupes de sécurité de l'utilisateur

Ajout dans Azure AD d'une claim de récupération des groupes de Security basé sur SamAccountName

## Revendications supplémentaires

Nom de revendication	Valeur
• <a href="http://schemas.microsoft.com/ws/2008/06/identity/claims/groups">http://schemas.microsoft.com/ws/2008/06/identity/claims/groups</a>	user.groups [SecurityGroup]
<a href="http://schemas.xmlsoap.org/ws/2005/05/identity/claims/emailaddress">http://schemas.xmlsoap.org/ws/2005/05/identity/claims/emailaddress</a>	user.mail
<a href="http://schemas.xmlsoap.org/ws/2005/05/identity/claims/givenname">http://schemas.xmlsoap.org/ws/2005/05/identity/claims/givenname</a>	user.givenname
<a href="http://schemas.xmlsoap.org/ws/2005/05/identity/claims/name">http://schemas.xmlsoap.org/ws/2005/05/identity/claims/name</a>	user.userprincipalname
<a href="http://schemas.xmlsoap.org/ws/2005/05/identity/claims/surname">http://schemas.xmlsoap.org/ws/2005/05/identity/claims/surname</a>	user.surname

1. Ajout de la revendication dans le fichier \conf\attributes\azureClaims.xml

```
<bean parent="shibboleth.TranscodingProperties">
  <property name="properties">
    <props merge="true">
      <prop key="id">azureGroups</prop>
      <prop key="transcoder">SAML2StringTranscoder</prop>
      <prop key="saml2.name">http://schemas.microsoft.com/ws/2008/06/identity/claims/
groups</prop>
      <prop key="saml2.nameFormat">urn:oasis:names:tc:SAML:2.0:attrname-
format:unspecified</prop>
      <prop key="displayName.en">Groups</prop>
      <prop key="description.en">Azure Groups of an account</prop>
    </props>
  </property>
</bean>
```

2. Autoriser dans l'attribute filter :\attribute-filter.xml

Ajout de la ligne suivante : <AttributeRule attributeID="azureGroups" permitAny="true" />

Dans le BLOC

```
<AttributeFilterPolicy id="FilterPolicyObject-Proxy-FromAzure-byIssuer-Type">
```

En dessous de

```
<AttributeRule attributeID="azureObjectidentifier" permitAny="true" />
```

3. Récupération de ces groupes dans attributes-resolver.xml :

```
<AttributeDefinition id="groups" xsi:type="Simple">
<InputDataConnector ref="passthroughAttributes" attributeNames="azureGroups" />
<DisplayName xml:lang="en">Groups</DisplayName>
<DisplayName xml:lang="fr">Groupes</DisplayName>
<DisplayDescription xml:lang="en">Groups</DisplayDescription>
<DisplayDescription xml:lang="fr">Groupes</DisplayDescription>
<AttributeEncoder xsi:type="SAML2String" name="urn:oid:1.3.6.1.4.1.5923.1.5.1.1"
friendlyName="groups"/>
</AttributeDefinition>
```

4. Ecriture d'un script CDATA qui permet de déterminer un attribut statique en fonction de l'appartenance au groupe :

```
<!-- eduPersonEntitlement -->
```

```
<AttributeDefinition id="eduPersonEntitlement" xsi:type="ScriptedAttribute">
```



```
<InputAttributeDefinition ref="groups"/>

<Script>

<![CDATA[

if (typeof groups != "undefined" && groups != null ){

// Config des groupes pour eduVPN

if (groups.getValues().contains("eduVPN") || groups.getValues().contains("ENS")){

eduPersonEntitlement.addValue("urn:mace:belnet.be:eduvpn:belnet:admin");

}

}

]}>

</Script>

</AttributeDefinition>

<!-- End of eduPersonEntitlement -->

<!-- eduPersonAffiliation -->

<AttributeDefinition id="eduPersonAffiliation" xsi:type="ScriptedAttribute">

<InputAttributeDefinition ref="groups"/>

<Script>

<![CDATA[

if (typeof groups != "undefined" && groups != null ){
```

```

if (groups.getValues().contains("ENS") || groups.getValues().contains("ADM") ||
groups.getValues().contains("DIR")){

eduPersonAffiliation.addValue("staff");

eduPersonAffiliation.addValue("student");

}

if (groups.getValues().contains("ETU")){

eduPersonAffiliation.addValue("student");

}

}

]]>

</Script>

</AttributeDefinition>

<!-- End of eduPersonAffiliation -->

```

#### 5. Autoriser le release de l'attribut dans Attribute-filter.xml

```

<AttributeRule attributeID="eduPersonEntitlement">

    <PermitValueRule xsi:type="ANY" />

</AttributeRule>

<AttributeRule attributeID="eduPersonAffiliation">

    <PermitValueRule xsi:type="ANY" />

</AttributeRule>

```

## 6 Renommer un IDP

- Changer DNS
- Changer /metadata/idp-metatada.xml
- Changer /conf/idp.properties
- Changer / etc/hostnames et hosts
- Renommer le Vhost apache et son contenu et refaire un a2ensite
- Changer URI dans App Azure AD
- Zabbix
- Backup sur BAR

## 7 Annexes

### 7.1 Annexe 1 : Contenu du fichier idp.yourdomain.be.conf pour Apache

```
# This is an example Apache2 configuration for a Shibboleth Identity Provider
# installed with IDEM Tutorials.
#
# Edit this file and:
# - Adjust "idp.yourdomain.be" with your IdP Full Qualified Domain Name
# - Adjust "ServerAdmin" email address
# - Adjust "CustomLog" and "ErrorLog" with Apache log files path (there are examples for Debian or
CentOS distribution)
# - Adjust "SSLCertificateFile", "SSLCertificateKeyFile" and "SSLCACertificateFile" with the correct file path

# SSL general security improvements should be moved in global settings
# OCSP Stapling, only in httpd/apache >= 2.3.3
SSLUseStapling on
SSLStaplingResponderTimeout 5
```

```
SSLStaplingReturnResponderErrors off

SSLStaplingCache shmcb:/var/run/ocsp(128000)

<VirtualHost *:80>

    ServerName "idp.yourdomain.be"

    Redirect permanent "/" "https://idp.yourdomain.be/"

</VirtualHost>

<IfModule mod_ssl.c>

    <VirtualHost _default_:443>

        ServerName idp.yourdomain.be:443

        ServerAdmin webmaster@yourdomain.be

        # Debian

        CustomLog /var/log/apache2/idp.yourdomain.be.log combined

        ErrorLog /var/log/apache2/ idp.yourdomain.be-error.log

        # Centos

        #CustomLog /var/log/httpd/idp.yourdomain.be.log combined

        #ErrorLog /var/log/httpd/idp.yourdomain.be.be-error.log

        DocumentRoot /var/www/html/idp.yourdomain.be

        SSLEngine On

        SSLProtocol All -SSLv2 -SSLv3 -TLSv1 -TLSv1.1

        SSLCipherSuite "EECDH+ECDSA+AESGCM EECDH+aRSA+AESGCM EECDH+ECDSA+SHA384
EECDH+ECDSA+SHA256 EECDH+aRSA+SHA384 EECDH+aRSA+SHA256 EECDH+aRSA+RC4 EECDH EDH+aRSA
RC4 !aNULL !eNULL !LOW !3DES !MD5 !EXP !PSK !SRP !DSS !RC4"

        SSLHonorCipherOrder on
```

```
# Disallow embedding your IdP's login page within an iframe and
# Enable HTTP Strict Transport Security with a 2 year duration
<IfModule headers_module>
    Header set X-Frame-Options DENY
    Header set Strict-Transport-Security "max-age=63072000 ; includeSubDomains ; preload"
</IfModule>

# Debian
SSLCertificateFile /etc/apache2/certs/star.yourdomain.be.cer
SSLCertificateKeyFile /etc/apache2/certs/star.yourdomain.be.key
    SSLCertificateChainFile /etc/apache2/certs/SectigoCA.cer

<IfModule mod_proxy.c>
    ProxyPreserveHost On
    RequestHeader set X-Forwarded-Proto "https"
    ProxyPass /idp http://localhost:8080/idp retry=5
    ProxyPassReverse /idp http://localhost:8080/idp retry=5

    <Location /idp>
        Require all granted
    </Location>
</IfModule>
</VirtualHost>
</IfModule>

# This virtualhost is only here to handle administrative commands for Shibboleth, executed from localhost
<VirtualHost 127.0.0.1:80>
```

```
ProxyPass /idp http://localhost:8080/idp retry=5
ProxyPassReverse /idp http://localhost:8080/idp retry=5
<Location /idp>
  Require all granted
</Location>
</VirtualHost>
```